

Section 1 Chemical Product and Company Identification

Page E1 of E2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

Boreal Science
399 Vansickle Road
St. Catharines, Ontario
L2S 3T4 Canada
Tel: (800) 387-9393

CHEMTREC 24 Hour Emergency USA
Phone Number (800) 424-9300
For laboratory and industrial use only.
Not for drug, food or household use.

Product	HEXANES
----------------	---------

Synonyms	n-Hexanes / Hexane / n-Hexane
-----------------	-------------------------------

Section 2 Hazards Identification

Signal word: DANGER

Pictograms: GHS02 / GHS07 / GHS08 / GHS09

Target organs: Central nervous system, Peripheral nervous system

**GHS Classification:**

Flammable liquid (Category 2)

Aspiration hazard (Category 1)

Skin irritation (Category 2)

STOT-SE (Category 3)

Reproductive toxicity (Category 2)

STOT-RE (Category 2)

Chronic aquatic (Category 2)

GHS Label information: Hazard statement(s):

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known

Physical hazards not otherwise classified (PHNOC) - Not Known

Precautionary statement(s):

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314: Get medical attention if you feel unwell.

P370+P378: In case of fire: Use dry chemical, CO₂, water spray or regular foam to extinguish.

P391: Collect spillage.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Section 3 Composition / Information on Ingredients

Chemical Name	CAS #	%	EINECS
n-Hexane	110-54-3	70%	203-777-6
Mixed isomers	Various	30%	Various

Section 4 First Aid Measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire Fighting Measures

Suitable Extinguishing Media: Dry chemical, CO₂, water spray or regular foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Section 6 Accidental Release Measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8 Exposure Controls / Personal Protection

Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
	Hexane	TWA: 50 ppm / 176 mg/m ³	TWA: 500 ppm / 1800 mg/m ³	TWA: 50 ppm / 180 mg/m ³

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: Work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical & Chemical Properties

Appearance: Clear, colorless liquid.	Evaporation rate (Butyl acetate = 1): 8.10	Partition coefficient: (n-octanol / water): Low Pow: 3.9
Odor: Mild odor.	Flammability (solid/gas): Data not available.	Auto-ignition temperature: Data not available.
Odor threshold: Data not available.	Explosion limits: Lower / Upper: 1.08% / 8.0%	Decomposition temperature: Data not available.
pH: Data not available.	Vapor pressure (mm Hg): 5.6 @ 100°F	Viscosity: Data not available.
Melting / Freezing point: Data not available	Vapor density (Air = 1): 3.0	Molecular formula: C ₆ H ₁₄
Boiling point: 63-68°C (145-156°F)	Relative density (Specific gravity): 0.660-0.690	Molecular weight: 86.18
Flash point: -22°C (-7°F) TOC	Solubility(ies): Negligible in water.	

Section 10 Stability & Reactivity

Chemical stability: Stable **Hazardous polymerization:** Will not occur.

Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizing, acids, bases, and selected amines.

Hazardous decomposition products: Oxides of carbon.

Section 11 Toxicological Information

Acute toxicity: Oral-mouse LD50: 5000 mg/kg ; Dermal-rabbit LD50: 3000 mg/kg

Skin corrosion/irritation: Data not available

Serious eye damage/irritation: Data not available

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenicity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: ⚠️ **WARNING!** : This product can expose you to Hexane, which is known to the State of California to cause birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available

Aspiration hazard: Yes

Potential health effects:

Inhalation: Dizziness, drowsiness, lethargy, headache, nausea, weakness, unconsciousness.

Ingestion: Aspiration hazard. Liquid can directly enter the lungs (aspirated) when swallowed or vomited. Serious lung damage and possible fatal chemical pneumonia can develop if this occurs.

Skin: Prolonged or repeated contact may cause dry skin, redness and pain.

Eyes: Contact causes redness and pain.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: MN9275000

Section 12 Ecological Information

Toxicity to fish: No data available

Toxicity to daphnia and other aquatic invertebrates: No data available

Toxicity to algae: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal Considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport Information (US DOT / CANADA TDG)

UN/NA number: UN1208

Shipping name: Hexanes

Hazard class: 3

Packing group: II

Reportable Quantity: Yes

Marine pollutant: No

Exceptions: Limited quantity equal to or less than 1 L

2016 ERG Guide # 128

Section 15 Regulatory Information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Hexanes	Listed	5000 lb (2270 kg)	D001	Listed	Not listed	⚠️ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Section 16 Other Information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Section 1 L'identification de produit chimique et de compagnie

Page F1 of F2



5100 West Henrietta Rd
PO Box 92912
Rochester, NY 14692-9012
Tel: (800) 962-2660

Boreal Science
399 Vansickle Road
St. Catharines, Ontario
L2S 3T4 Canada
Tel: (800) 387-9393

**CHEMTREC 24 Numéros De Téléphone De
Secours D'Heure (800) 424-9300**
Pour l'usage industriel et de laboratoire seulement.
Pas pour l'usage de drogue, de nourriture ou de ménage.

Produit	HEXANES
Synonymes	n-Hexanes / Hexane / n-Hexane

Section 2 Identification De Risques

Mention d'avertissement: DANGER

Pictogrammes: GHS02 / GHS07 / GHS08 / GHS09

Les organes cibles: Le système nerveux central, le système nerveux périphérique



Classification par le GHS:

Liquide inflammable (Catégorie 2)

Aspiration hazard (Catégorie 1)

Skin irritation (Catégorie 2)

STOT-SE (Catégorie 3)

Reproductive toxicity (Catégorie 2)

STOT-RE (Catégorie 2)

Chronic aquatic (Catégorie 2)

Renseignements sur l'étiquette GHS: Mention de danger(s):

H225: Liquide et vapeurs très inflammables.

H304: Peut être mortel en cas d'ingestion et de pénétration dans les voies respiratoires.

H315: Provoque une irritation cutanée.

H336: Peut provoquer somnolence ou des vertiges.

H361f: Susceptible de nuire à la fertilité.

H373: Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.

H411: Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Dangers non classés autrement:

Dangers pour la santé non classés ailleurs (HHNOC) - pas connu

Dangers physiques non classés autrement (PHNOC) - pas connu

Section 3 Composition / Information Sur Des Ingrédients

Nommé Chimique	# CAS	%	EINECS
n-Hexane	110-54-3	70%	203-777-6
Mélange d'isomères	Divers	30%	Divers

Section 4 Mesures De Premiers Soins

INGESTION: PEUT ÊTRE NOCIF EN CAS D'INGESTION. Appeler un médecin ou un centre antipoison immédiatement. Provoquer le vomissement seulement si elle est informée par le personnel compétent médicaux. Ne jamais rien donner par la bouche à une personne inconsciente.

INHALATION: PEUT ÊTRE NOCIF EN CAS D'INHALATION. IRRITE LES VOIES RESPIRATOIRES. Sortir au grand air. Si elle ne respire pas, pratiquer la respiration artificielle. Si la respiration est difficile, donner de l'oxygène. Obtenir des soins médicaux.

CONTACT AVEC LES YEUX: CAUSE L'IRRITATION DES YEUX. Vérifier et enlever les lentilles de contact. Rincer abondamment à l'eau pendant au moins 15 minutes, en soulevant les paupières inférieures et supérieures de temps en temps. Obtenez une attention médicale immédiate.

ABSORPTION PAR LA PEAU: PEUT ÊTRE NOCIF EN CAS D'ABSORPTION PAR LA PEAU. PEUT CAUSER UNE IRRITATION DE LA PEAU. Enlever les vêtements contaminés. Rincer soigneusement avec du savon doux et d'eau. En cas d'irritation, consulter un médecin.

Section 5 Mesures De Lutte Contre l'Incendie

Moyens d'extinction: Produit chimique sec, CO₂, eau pulvérisée ou mousse ordinaire.

Actions de protection pour les sapeurs-pompiers: En cas d'incendie, porter un appareil respiratoire NIOSH / MSHA approuvé autonome et un équipement complet de protection. Utiliser un jet d'eau pour maintenir incendie refroidir les conteneurs exposés.

Dangers spécifiques: En cas d'incendie, des gaz irritants et très toxiques peuvent être générés par la décomposition thermique ou la combustion. Les vapeurs peuvent former des mélanges explosifs avec l'air. Vapeurs peuvent se déplacer jusqu'à une source d'ignition et revenir. Les conteneurs peuvent exploser lorsqu'ils sont chauffés

Section 6 Mesures De Déchargement Accidentel

Précautions personnelles: Évacuer le personnel vers la zone sûre. Utiliser un équipement de protection personnelle comme indiqué dans la Section 8. Assurer une ventilation adéquate.

Précautions environnementales: Éviter tout ruissellement vers les égouts pluviaux et les fossés qui aboutissent aux voies navigables.

Confinement et de nettoyage: Absorbent avec le matériel sec inerte, balayez ou nettoyez à l'aspirateur vers le haut et placez dans un récipient approprié pour la disposition appropriée. Laver la zone de déversement avec du savon et de l'eau.

Précautions pour la manutention en toute sécurité: Lire l'étiquette sur le contenant avant d'utiliser. Ne pas porter de lentilles cornéennes lorsque vous travaillez avec des produits chimiques. Tenir hors de portée des enfants. Éviter tout contact avec les yeux, la peau et les vêtements. Ne pas inhaler les vapeurs, les embruns ou le brouillard. Utiliser avec une ventilation adéquate. Éviter l'ingestion. Bien se laver après la manipulation. Retirer et laver les vêtements avant de les réutiliser.

Conditions de stockage: Stocker dans un endroit frais et bien aéré, loin des substances incompatibles. Substance loin des sources d'allumage.

Section 8 Commandes D'Exposition / Protection Personnelle

Limites d'exposition:	Nommé Chimique	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)
		Hexane	TWA: 50 ppm / 176 mg/m ³	TWA: 500 ppm / 1800 mg/m ³

Contrôles d'ingénierie: Les installations d'entreposage ou d'utilisation de ce matériel doit être équipé d'une douche oculaire et une douche de sécurité et le matériel d'extinction d'incendie. Le personnel doit porter des lunettes de sécurité, des lunettes, ou un écran facial, une blouse de laboratoire ou tablier, des gants protecteurs appropriés. Utiliser une ventilation adéquate pour maintenir les concentrations atmosphériques faible.

Protection respiratoire: Travaillez dans le capot de vapeur ou portez un respirateur de NIOSH/MSHA-approved.

Section 9 Propriétés Physiques Et Chimiques

Apparence: Clair, liquide incolore.

Odeur: Légère odeur.

Seuil de l'odeur: Données non disponibles.

pH: Données non disponibles.

Point de fusion / congélation: Données non disponibles

Point d'ébullition: 63-68°C (145-156°F)

Point d'éclair: -22°C (-7°F) TOC

Taux d'évaporation (Acetate de butylique = 1): 8.10

Inflammabilité (solide / gaz): Données non disponibles.

Limites d'explosivité: Bas / Max: 1.08% / 8.0%

Pression de vapeur (mm Hg): 5.6 @ 100°F

Densité de vapeur (Air = 1): 3.0

Densité relative (gravité spécifique): 0.660-0.690

Solubilité (s): Négligeable dans l'eau.

Coefficient de partage: (n-octanol / water): Low Pow: 3.9

Auto-inflammation: Données non disponibles

Température de décomposition: Données non disponibles.

Viscosité: Données non disponibles.

Formule moléculaire: C₆H₁₄

Poids moléculaire: 86.18

Section 10 Stabilité Et Réactivité

Stabilité chimique: Stable

Polymérisation dangereuse: N'aura pas lieu.

Conditions à éviter: Les températures excessives, la chaleur, étincelles, flamme nue et d'autres sources d'allumage.

Matières incompatibles: Les matériaux de oxydation forts, l'acides, des bases et l'amines sélectionnées.

Produits dangereux de décomposition: Oxydes de carbones.

Section 11 L'Information Toxicologique

Toxicité aiguë: Oral-mouse LD50: 5000 mg/kg ; Dermal-rabbit LD50: 3000 mg/kg

La corrosion de la peau et l'irritation: Données non disponibles

Des lésions oculaires graves / irritation: Données non disponibles

Respiratoire ou sensibilisation de la peau: Données non disponibles

Mutagenicité des cellules germinales: Données non disponibles

Cancérogène: Données non disponibles

NTP: Aucun composant de ce produit présent à des niveaux supérieurs ou égaux à 0,1% n'a été identifié comme cancérogène reconnu ou présumé par NTP.

IARC: Aucun composant de ce produit présent à des niveaux supérieurs ou égaux à 0,1% n'a été identifié comme cancérogène probable, possible ou confirmé par IARC.

OSHA: Aucun composant de ce produit présent à des niveaux supérieurs ou égaux à 0,1% n'a été identifié comme cancérogène ni comme cancérogène possible par OSHA.

Reproductive toxicity: Données non disponibles

STOT-exposition unique: La substance ou le mélange est classé comme toxique pour certains organes cibles, exposition unique, catégorie 3 avec des effets narcotiques.

STOT-une exposition répétée: Données non disponibles

Risque d'aspiration: Yes

Effets d'une surexposition:

Inhalation: Étourdissements, de la somnolence, de la léthargie, des maux de tête, nausée, faiblesse, perte de conscience.

Ingestion: Risque d'aspiration. Le liquide peut entrer directement dans les poumons (aspiration) en cas d'ingestion ou de vomissements. Dommages pulmonaires graves et une pneumonie chimique fatale possible peut se développer si cela se produit.

Peau: Un contact prolongé ou répété peut dessécher la peau, rougeur et douleur.

Yeux: Le contact provoque une rougeur et douleur.

Les signes et les symptômes de l'exposition: Voir les effets sanitaires potentiels ci-dessus.

Informations complémentaires: RTECS #: MN9275000

Section 12 L'Information Écologique

Toxicité pour les poissons: Pas de données disponible

Toxicité pour les daphnies et autres invertébrés aquatiques: Pas de données disponible

Toxicité pour les algues: Pas de données disponible

Persistance et dégradabilité: Pas de données disponible

Potentiel de bioaccumulation: Pas de données disponible

Mobilité dans le sol: Pas de données disponibles

Évaluation PBT et vPvB: Pas de données disponibles

Autres effets indésirables: Un danger pour l'environnement ne peut pas être exclu dans l'éventualité d'une manipulation ou d'élimination.

Section 13 Considérations De Disposition

Ces lignes directrices sont destinées à l'élimination de la disposition d'un catalogue de taille seules les quantités. Les règlements fédéraux peuvent s'appliquer aux contenants vides. Des réglementations nationales et / ou local peut être différent. Éliminer conformément à toutes les réglementations locales, provinciales et fédérales ou d'un contrat avec une agence élimination des produits chimiques sous licence.

Section 14 L'Information De Transport (US DOT / CANADA TMD)

Numéro UN / NA: UN1208

Nom d'expédition: Hexanes

Classe de danger: 3

Groupe d'emballage: II

Quantité à déclarer: Oui

Polluant marin: No

Exceptions: Quantité limitée égale à ou moins de 1 L

2016 ERG Guide #: 128

Section 15 L'Information De Normalisation

Un produit chimique est considéré comme inscrit si le numéro CAS pour la forme anhydre est sur la liste d'inventaire.

Composant	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL
Hexanes	Listed	5000 lb (2270 kg)	D001	Listed	Not listed

Section 16 L'autre Information

Les informations contenues dans ce document sont fournis sans garantie d'aucune sorte. Les employeurs devraient considérer cette information seulement comme complément à d'autres informations recueillies par eux et doivent prendre des décisions indépendantes de la pertinence et l'exhaustivité de l'information de toutes les sources afin d'assurer une utilisation correcte de ces matériaux et de la sécurité et la santé des employés. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.