

SAFETY DATA SHEET

Version 6.27
Revision Date 08/06/2024
Print Date 08/07/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Ethyl acetate
Product Number : 270989
Brand : Sigma-Aldrich
Index-No. : 607-022-00-5
CAS-No. : 141-78-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances
Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.
3050 SPRUCE ST
ST. LOUIS MO 63103
UNITED STATES
Telephone : +1 314 771-5765
Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225
Eye irritation (Category 2A), H319
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Sigma-Aldrich - 270989

Page 1 of 11

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225

Highly flammable liquid and vapor.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Precautionary Statements

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P261

Avoid breathing mist or vapors.

P264

Wash skin thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313

If eye irritation persists: Get medical advice/ attention.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	:	C ₄ H ₈ O ₂
Molecular weight	:	88.11 g/mol
CAS-No.	:	141-78-6
EC-No.	:	205-500-4
Index-No.	:	607-022-00-5

Sigma-Aldrich - 270989

Page 2 of 11

The life science business of Merck KGaA, Darmstadt, Germany operates as MilliporeSigma in the US and Canada

**MILLIPORE
SIGMA**

Component	Classification	Concentration
ethyl acetate		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

No data available

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides
Combustible.

5.3 Advice for firefighters

No data available

5.4 Further information

No data available

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For personal protection see section 8.

6.2 Environmental precautions

No data available

6.3 Methods and materials for containment and cleaning up

No data available

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

No data available

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethyl acetate	141-78-6	TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	400 ppm 1,400 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	400 ppm 1,400 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	400 ppm 1,400 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	1468 mg/m ³
Workers	Inhalation	Acute local effects	1468 mg/m ³
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	734 mg/m ³
Workers	Inhalation	Long-term local effects	734 mg/m ³
Consumers	Inhalation	Acute local effects, Acute systemic effects	734 mg/m ³
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	367 mg/m ³
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d

Consumers	Inhalation	Long-term local effects	367 mg/m ³
-----------	------------	-------------------------	-----------------------

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.24 mg/kg
Sea water	0.026 mg/l
Fresh water	0.26 mg/l
Sea sediment	0.125 mg/kg
Fresh water sediment	1.25 mg/kg

8.2 Exposure controls

Personal protective equipment

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Butoject® (KCL 898)

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---------------------------------|---|
| a) Appearance | Form: clear, liquid
Color: colorless |
| b) Odor | fruity |
| c) Odor Threshold | 0.1 ppm |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/ range: -84 °C (-119 °F) |

Sigma-Aldrich - 270989

Page 5 of 11

f) Initial boiling point and boiling range	76.5 - 77.5 °C 169.7 - 171.5 °F
g) Flash point	-4 °C (25 °F) - closed cup - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 11.5 %(V) Lower explosion limit: 2.1 %(V)
k) Vapor pressure	No data available
l) Vapor density	3.04
m) Density	0.90 g/cm ³ at 20 °C (68 °F)
Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	log Pow: 0.73 - Bioaccumulation is not expected., (Lit.)
p) Autoignition temperature	No data available
q) Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r) Viscosity	No data available
s) Explosive properties	Not classified as explosive.
t) Oxidizing properties	none

9.2 Other safety information

Relative vapor density	3.04
------------------------	------

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Exothermic reaction with:

Fluorine

chlorosulfonic acid

Strong oxidizing agents

fuming sulfuric acid

Risk of explosion with:
lithium aluminium hydride
Alkali metals
hydrides
Alkaline earth metals
Violent reactions possible with:
Strong acids and strong bases

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5,620 mg/kg

Remarks: (RTECS)

Inhalation: No data available

LD50 Dermal - Rabbit - male - > 20,000 mg/kg

Remarks: (ECHA)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (IUCLID)

Serious eye damage/eye irritation

Remarks: Causes serious eye irritation.

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: UDS (Unscheduled DNA synthesis assay)

Test system: Escherichia coli

Metabolic activation: with and without metabolic activation

Method: US-EPA

Result: negative

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative
Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Test Type: Micronucleus test
Species: Chinese hamster
Cell type: Red blood cells (erythrocytes)
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 92 Days - NOAEL (No observed adverse effect level) - 900 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,600 mg/kg

RTECS: AH5425000

Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 230 mg/l - 96 h (US-EPA)
Toxicity to algae	static test NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	Remarks: (IUCLID) (ethyl acetate)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	semi-static test NOEC - Daphnia magna (Water flea) - 2.4 mg/l - 21 d (OECD Test Guideline 211)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 20 d Result: ca.69 % - Readily biodegradable. Remarks: (ECHA)
Theoretical oxygen demand	1,820 mg/g Remarks: (Lit.)

12.3 Bioaccumulative potential

Bioaccumulation	Leuciscus idus melanotus - 3 Days at 22.5 °C(ethyl acetate)
	Bioconcentration factor (BCF): 30

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

No data available

SECTION 14: Transport information**DOT (US)**

UN number: 1173 Class: 3 Packing group: II
Proper shipping name: Ethyl acetate
Reportable Quantity (RQ): 5000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1173 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: ETHYL ACETATE

IATA

UN number: 1173 Class: 3 Packing group: II
Proper shipping name: Ethyl acetate

SECTION 15: Regulatory information**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ethyl acetate	141-78-6	5000	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Massachusetts Right To Know**

ethyl acetate 141-78-6

Pennsylvania Right To Know

ethyl acetate 141-78-6

Sigma-Aldrich - 270989

Page 10 of 11

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16: Other information

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.27

Revision Date: 08/06/2024

Print Date: 08/07/2024