

SAFETY DATA SHEET

Version 6.11 Revision Date 03/02/2024 Print Date 06/23/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Silver nitrate

Product Number : 209139 Brand : SIGALD

Index-No. : 047-001-00-2 CAS-No. : 7761-88-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Oxidizing solids (Category 2), H272 Corrosive to Metals (Category 1), H290 Skin corrosion (Category 1A), H314

SIGALD - 209139

Page 1 of 12



Serious eye damage (Category 1), H318
Reproductive toxicity (Category 1B), H360
Short-term (acute) aquatic hazard (Category 1), H400
Long-term (chronic) aquatic hazard (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram Signal Word Danger **Hazard Statements** H272 May intensify fire; oxidizer. H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. May damage fertility or the unborn child. H360 H410 Very toxic to aquatic life with long lasting effects. **Precautionary Statements** P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat. P220 Keep/Store away from clothing/ combustible materials. Take any precaution to avoid mixing with combustibles. P221 P234 Keep only in original container. P260 Do not breathe dust. Wash skin thoroughly after handling. P264 P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable P304 + P340 + P310 for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + IF IN EYES: Rinse cautiously with water for several minutes. P310 Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P390 Absorb spillage to prevent material damage. P391 Collect spillage. P405 Store locked up.

Store in corrosive resistant container with a resistant inner

Dispose of contents/ container to an approved waste disposal

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

plant.

SIGALD - 209139



Page 2 of 12

P406

P501

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : AgNO₃

Molecular weight : 169.87 g/mol CAS-No. : 7761-88-8 EC-No. : 231-853-9 Index-No. : 047-001-00-2

Component	Classification	Concentration		
Silver nitrate				
Silver nitrate	Ox. Sol. 2; Met. Corr. 1; Skin Corr. 1A; Eye Dam. 1; Repr. 1B; Aquatic Acute 1; Aquatic Chronic 1; H272, H290, H314, H318, H360, H400, H410 Concentration limits: >= 1 %: Met. Corr. 1, H290; 68 %: Ox. Sol. 2, H272; M-Factor - Aquatic Acute:	<= 100 %		
	1,000 - Aquatic Chronic: 100			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

SIGALD - 209139

Page 3 of 12

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

Silver/silver oxides

Container explosion may occur under fire conditions.

Not combustible.

Has a fire-promoting effect due to release of oxygen.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SIGALD - 209139

Page 4 of 12



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

No metal containers.

Tightly closed. Keep locked up or in an area accessible only to qualified or authorized persons. Do not store near combustible materials.

Light sensitive.

Storage class

Storage class (TRGS 510): 5.1B: Oxidizing hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters



Component	CAS-No.	Value	Control parameters	Basis
Silver nitrate	7761-88-8	TWA	0.01 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.01 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		TWA	0.01 mg/m3	USA. NIOSH Recommended Exposure Limits
		PEL	0.01 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Body Protection

protective clothing

Respiratory protection

Recommended Filter type: Filter type P3

SIGALD - 209139



The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

a) Appearance Form: solid

Color: colorless

b) Odor odorless

c) Odor Threshold Not applicable d) pH No data available

e) Melting Melting point/range: 212 °C (414 °F) - dec. point/freezing point

Initial boiling point and boiling range

440 °C 824 °F - Decomposes on heating.

g) Flash point ()Not applicable h) Evaporation rate No data available Flammability (solid, No data available

gas)

No data available

Upper/lower j) flammability or explosive limits

k) Vapor pressure No data available Vapor density No data available m) Density 4.350 g/cm3

No data available Relative density n) Water solubility No data available

o) Partition coefficient:

n-octanol/water

Not applicable for inorganic substances

p) Autoignition No data available temperature

q) Decomposition temperature

No data available

SIGALD - 209139



r) Viscosity No data availables) Explosive properties No data available

t) Oxidizing properties The substance or mixture is classified as oxidizing with the

category 2.

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) . Decomposes on exposure to light.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Light.

no information available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral: No data available
Inhalation: No data available
Dermal: No data available

Skin corrosion/irritation

Skin - reconstructed human epidermis (RhE) Result: Causes severe burns. - 3 - 60 min

(OECD Test Guideline 431)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye damage.

Remarks: (ECHA)

Remarks: Risk of permanent damage due to staining of the cornea.

Respiratory or skin sensitization

No data available

SIGALD - 209139

Millipore SigMa

Germ cell mutagenicity

Test Type: Micronucleus test Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: Positive results were obtained in some in vitro tests.

Test Type: Micronucleus test

Species: Rat

Application Route: Gavage

Method: OECD Test Guideline 474

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 52 Days - NOAEL (No observed adverse effect level) - >= 250 mg/kg

RTECS: VW4725000

May cause argyria (a slate-gray or bluish discoloration of the skin and deep tissues due to the deposit of insoluble albuminate of silver)., Absorption into the body leads to the formation of methemoglobin which in sufficient concentration causes cyanosis. Onset may be delayed 2 to 4 hours or longer.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SIGALD - 209139

Page 9 of 12



SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish semi-static test LC50 - Pimephales promelas (fathead minnow) -

0.0012 mg/l - 96 h

(US-EPA)

Toxicity to daphnia and other aquatic

semi-static test EC50 - Daphnia magna (Water flea) - 0.00022 mg/l

- 48 h

invertebrates

Remarks: (ECHA)

static test ErC50 - Raphidocelis subcapitata (freshwater green alga) -Toxicity to algae

0.00252 mg/l - 72 h

(OECD Test Guideline 201)

static test EC10 - Raphidocelis subcapitata (freshwater green alga) -

0.00046 mg/l - 72 h (OECD Test Guideline 201)

Toxicity to

flow-through test NOEC - Pimephales promelas (fathead minnow) -

fish(Chronic toxicity) 0.000351 mg/l - 34 d

Remarks: (ECHA)

Toxicity to daphnia and other aquatic

semi-static test EC10 - Daphnia magna (Water flea) - 0.0027 mg/l -

invertebrates(Chronic Remarks: (ECHA)

21 d

toxicity)

12.2 Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 41 d

at 20 °C(Silver nitrate)

Bioconcentration factor (BCF): 70

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SIGALD - 209139

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 1493 Class: 5.1 Packing group: II

Proper shipping name: Silver nitrate Reportable Quantity (RQ): 1 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1493 Class: 5.1 Packing group: II EMS-No: F-A, S-Q

Proper shipping name: SILVER NITRATE

Marine pollutant : yes

IATA

UN number: 1493 Class: 5.1 Packing group: II

Proper shipping name: Silver nitrate

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date Silver nitrate 7761-88-8 1993-02-16

SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard

Massachusetts Right To Know Components

CAS-No. Revision Date Silver nitrate 7761-88-8 1993-02-16

Pennsylvania Right To Know Components

Silver nitrate CAS-No. Revision Date 7761-88-8 1993-02-16

SIGALD - 209139 Page 11 of 12

Millipore SigMa

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.11 Revision Date: 03/02/2024 Print Date: 06/23/2024

SIGALD - 209139 Page 12 of 12

