



CALCIUM OXIDE

MSDS Number: C0462 --- Effective Date: 12/08/96

1. Product Identification

Synonyms: Lime unslaked; lime burnt; quicklime; calx; lime purified
CAS No.: 1305-78-8
Molecular Weight: 56.08
Chemical Formula: CaO
Product Codes:
J.T. Baker: 1410, 1414
Mallinckrodt: 0204, 4243, 4248

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Calcium Oxide	1305-78-8	100%	Yes

3. Hazards Identification

Emergency Overview

DANGER! CAUSES SEVERE IRRITATION AND BURNS TO EVERY AREA OF CONTACT. HARMFUL IF SWALLOWED OR INHALED.

J.T. Baker SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 1 - Slight
Flammability Rating: 0 - None
Reactivity Rating: 1 - Slight
Contact Rating: 2 - Moderate
Lab Protective Equip: GOGGLES; LAB COAT
Storage Color Code: Orange (General Storage)

Potential Health Effects

Inhalation:

Inhalation of dust is highly irritating and possibly corrosive to the upper respiratory tract. May cause coughing, sneezing, labored breathing, and possibly burns with perforation of the nasal septum.

Ingestion:

Corrosive. May attack the esophagus. Abdominal pain, nausea, vomiting may result. May cause serious alkali burns in mouth and throat.

Skin Contact:

Irritant; may cause severe corrosive damage.

Eye Contact:

Severe irritant, may damage eye tissues. Causes redness, tearing, blurred vision, pain.

Chronic Exposure:

Chronic inhalation of dust may cause inflammation of the respiratory passages, ulcers of the mucous membranes, and possible perforation of nasal septum.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems or impaired respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

DO NOT INDUCE VOMITING! Give large quantities of water or milk if available. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician, immediately. Wash clothing before reuse.

Eye Contact:

Wash thoroughly with running water. Get medical advice if irritation develops.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard. Lime and water can react exothermically with sufficient heat to ignite combustible materials in certain instances.

Explosion:

Not considered to be an explosion hazard. The combination of lime and water at high temperatures may be explosive.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust.

7. Handling and Storage

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. This strongly alkaline material will swell and generate heat when moistened and could burst container. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):

5 mg/m³ (TWA).

-ACGIH Threshold Limit Value (TLV):

2 mg/m³ (TWA)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, a full facepiece respirator with dust/mist filter may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

White to slightly yellowish powder.

Odor:

Odorless.

Solubility:

Slightly soluble in water with release of heat, formation of calcium hydroxide.

Specific Gravity:

3.37

pH:

12.5 Saturated solution in water

% Volatiles by volume @ 21C (70F):

0

Boiling Point:

2850C (5162F)

Melting Point:

2572C (4662F)

Vapor Density (Air=1):

1.9

Vapor Pressure (mm Hg):

No information found.

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable at room temperature in sealed containers.

Hazardous Decomposition Products:

No hazardous decomposition products.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Water, acids, humid air, hydrogen fluoride, phosphorous pentoxide, boric oxide, steam, many organic substances.

Conditions to Avoid:

Air, moisture, and incompatibles.

11. Toxicological Information

Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Calcium Oxide (1305-78-8)	No	No	None

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

This material is expected to be toxic to aquatic life.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Not regulated.

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----				
Ingredient	TSCA	EC	Japan	Australia
Calcium Oxide (1305-78-8)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----				
Ingredient	Korea	DSL	--Canada-- NDSL	Phil.
Calcium Oxide (1305-78-8)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----				
Ingredient	-SARA 302-		-----SARA 313-----	
	RQ	TPQ	List	Chemical Catg.
Calcium Oxide (1305-78-8)	No	No	No	No

-----\Federal, State & International Regulations - Part 2\-----			
Ingredient	CERCLA	-RCRA- 261.33	-TSCA- 8(d)
Calcium Oxide (1305-78-8)	No	No	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
 SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No
 Reactivity: Yes (Pure / Solid)

Australian Hazchem Code: No information found.

Poison Schedule: No information found.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 1 Flammability: 0 Reactivity: 1

Label Hazard Warning:

DANGER! CAUSES SEVERE IRRITATION AND BURNS TO EVERY AREA OF CONTACT. HARMFUL IF SWALLOWED OR INHALED.

Label Precautions:

Do not get in eyes, on skin, or on clothing.

Do not breathe dust.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes.

Wash clothing before reuse. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth

to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In all cases call a physician.

Product Use:

Laboratory Reagent.

Revision Information:

New 16 section MSDS format, all sections have been revised.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Strategic Services Division

Phone Number: (314) 539-1600 (U.S.A.)